

Leica Jogger Series
Automatic Levels -Fit for
Work



SITE PROOF
by Leica Geosystems

- when it has to be **right**





Building and
Civil Engineering



Profiling



Landscaping



Area Leveling

Fit for Work -
Great features and great
performance

- Choice of magnification:
20x/24x/28x or 32x
- Automatic, air-damped
compensator
- Smooth, double-sided
endless fine drive for
easy and precise targeting
- Horizontal circle with
360° division



Fit for Work -
Quality and Endurance

- Water resistant (IP54) for
instrument use under harsh
environmental conditions
- 1 year warranty and access
to the worldwide Leica
Geosystems network of
service and support
centers



Fit for Work -
Great Jogger package
Tripod and staff are
important parts of any
levelling equipment.
Get better results with
approved original Leica
Geosystems tripods and
staffs. Ask for the
original Leica Jogger
package.

Leica Jogger	20	24	28	32
Standard deviation per 1 km double-run leveling	2.5 mm	2.0 mm		
Telescope				
Telescope image	upright			
Magnification	20 x	24 x	28 x	32 x
Clear objective lens	36 mm			
Shortest focusing distance	<1.0 m			
Field of view at 100 m	<2.1 m			
Multiplication constant	100			
Additive constant	0			
Compensator				
Working range	± 15'			
Setting accuracy (standard deviation)	<0.5''			
Circular bubble	8'/2 mm			
Horizontal circle				
Graduation	360°			
Interval	1°			
Weight (net)	1.5 kg			
Operating temperature range	-20°C to +40°C			

Illustrations, descriptions and technical specifications are not
binding and may change.
Copyright © Leica Geosystems AG, Heerbrugg, Switzerland, 2010.

Authorized **Leica Geosystems** Distributor

Lasco Laser & Instrument Co.
3220 Jefferson Ave
Grand Rapids, MI 49548
www.lascolaser.com
866-374-5428

Leica Geosystems AG
Heerbrugg, Switzerland
www.leica-geosystems.com

- when it has to be **right**

Leica
Geosystems